

Slasher – Single Cutting Head



QUEENSLAND

5 Terrence Road
Brendale
Queensland
Australia 4500

Telephone:
+61 7 3490 5100

Facsimile:
+ 61 7 3205 7873
Email:
sales@hydrapower.com.au

Hydrapower's 1500mm cut, **7601 Hydraulic Slasher** Attachment is provided with quick attach frame to suit the carrier machine. The quick attach frame pivots on two bosses, allowing you to crowd the quick hitch forward when slashing to let the slasher deck follow the contours of the ground.

The cutting height can be set between 40mm and 125mm, and set by skids on the slasher deck. A jockey wheel on the front of the slasher helps support the attachment. Debris chains fitted to the front and rear of the deck assist in protecting the operator and other personnel from flying debris.

The cutter bar is driven via the hydraulics of the skid steer loader through a hydraulic motor and right-angle drive gearbox. A cross port relief valve is fitted directly to the motor to protect it and the gearbox against sudden stops if the cutting blade should abruptly stop or slow down. The step-on ratio of the gearbox is 1:19, which gives an output speed of 360 rpm at 65 l/min. The tip speed at this rpm is 56 metres/sec (11000 feet/min).

The cutter bar has a 20mm top plate that is shaped to act as "stump jump" so that impact from hidden objects in the grass is reduced. 16mm thick double edge blades are fitted.

OPERATING PRESSURE:	138 - 207 bar (2000 - 3000 PSI)
OPERATING FLOW RATE:	60 - 75 l/min (16 - 20 GPM)
MASS:	375 kg